

Forward Port for GCOM GN2000-04GS-2VT

 Type 192.168.1.1 then press Enter, type Username = admin, Password = password then press Login

E) Home Gateway × → C □ 192.168.1.1	Θ - □
-G-COM	Home Gateway
Username	admin
Password	••••••
	Login
Copyright © 2017, GC	COM Technologies Co., Ltd. All Rights Reserved.



2. On the top select Security Setup and then Security > Port Forwarding

C 🛈 ไม่ปลอดภัย 192.16	1.1/index.html
G-COM TECHNOLOGY	Gateway Advanced Setup Vibilities
Management Password GPON Password (SLID)	Port Forwarding Port forwarding function forwards WAN applications to LAN devices. Multiple port forwarding rules are supported.
GPON Password (LOID) Remote Web	1. Set an application name. Application Name Customer Settings
IPv4 Firewall IPv6 Firewall MAC Filtering Website Filtering	2. Select LAN device, or manually enter an IP address. Device Manually Enter IP Address IP Address
Port Forwarding Port Trigger DMZ Hosting UPnP	3. Enter LAN side TCP/UDP port. TCP/UDP Port
	4. Select protocol. Protocol TCP ▼
	5. Enter WAN side TCP/UDP port range. Starting Port
	6. Select WAN connection. WAN Connection 1_INTERNET_TR069_R_VID_100 •
	7. Click "Add" to save your settings.
	Port Forwarding List Application Name LAN IP Protocol LAN Port WAN Port Range Edit

true

- 3. Check the settings as follows:
 - Application Name: select Customer Settings
 - Device: select device or enter IP Address at IP Address space
 - TCP/UDP Port: enter Port to Forward
 - Protocol: select as desired
 - Starting Port and Ending Port: enter Port to forward
 - WAN Connection: select 1_INTERNET_TR069_INTERNET_R_VID_100
 - Press Add

Application Name	Customer Settings	
2. Select LAN device. o	r manually enter an IP address.	
Device	Manually Enter IP Address	
IP Address	192.168.1.33	
3. Enter LAN side TCP/	UDP port.	
TCP/UDP Port	81	
4. Select protocol.		
Protocol	TCP V	
5. Enter WAN side TCP	/UDP port range.	
Starting Port	81	
Ending Port	81	
6. Select WAN connect	ion.	
WAN Connection	1_INTERNET_TR069_R_VID_100 V	
7. Click "Add" to save	your settings.	

TRUE CORPORATION PUBLIC COMPANY LIMITED 18 TRUE TOWER, RATCHADAPHISEK ROAD, HUAI KHWANG, BANGKOK 10310 THAILAND WWW.TRUECORP.CO.TH



E Home Gateway X							Θ -			×
C () ไม่ปลอดภัย 192.168.1.1/in	dex.html							7	☆	:
	4. Select protocol.									-
	Protocol		TCP	,						
	5. Enter WAN side TCP/UDP port range.									
	Starting Port									
	Ending Port									
	6. Select WAN connection.									
	WAN Connection	1_INT	ERNET_	TR069_R_VID	0_100 ▼					
	7. Click "Add" to save your settings.									
	Add									
	Port Forwarding List									
	Application Name	LAN IP	Protocol	LAN Port	WAN Port Range	Edit				
	Customer Settings	192.168.1.33	TCP	81	81	Edit	Remove			
	Copyright © 2017	, GCOM Technologi	es Co., Ltd. A	II Rights	Reserved.					
4										F

4. Once completed, setup information will be shown in below table